

Technical Data Sheet

HAGUDOSTA[®] Riser pipe (ZSM, PN 16)



Product description:

Traditional riser pipe with pull-resistant plug-in sleeve connection according to DIN 4945-1, **with two O-rings, two shear bars** and anti-twist bars

Product properties:

- Material: Steel with HAGULIT[®] coating
- Construction lengths: 1-5 m
- Connection type: ZSM
- Pressure rating: PN 16

Advantages of the product:

- Fast assembly
- Slim connection

Versions:

Nominal width [DN]	Wall thickness [mm]	Outer pipe Ø [mm]	Outer-Ø sleeve [mm]
50	2.9	60.3	84
65	2.9	76.1	100
80	2.9	88.9	115
100	3.2	114.3	141
125	3.6	139.7	170
150	4.0	168.3	202
175	4.0	193.7	229
200	4.5	219.1	255
250	5.0	273.0	310

Weight [kg]:

Nominal width [DN]	1.0 m	2.0 m	3.0 m	4.0 m	5.0 m
50	6.4	10.7	15.0	19.3	23.6
65	7.8	13.3	18.8	24.3	29.8
80	9.9	16.3	22.8	29.2	35.7
100	12.5	21.4	30.3	39.2	48.1
125	16.0	28.3	40.6	52.8	65.1
150	22.2	38.6	55.0	71.4	87.8
175	26.9	45.9	64.9	83.9	102.9
200	36.3	63.1	89.9	116.7	143.5
250	44.0	77.5	111.0	144.5	178.0

